DECOBASE

PRODUCT DATA SHEET

UPDATE: 01.01.2022

BRAND **PRIMACOL®** DECORATIVE

PRODUCT **Decobase**

Latex paint for indoor use. Paint for decorating system.



- Matt
- Washable

PACK **1l 5l**

PROPERTIES Decobase is a latex emulsion paint for indoor walls and ceilings. It is characterized by excellent coverage, durability and resistance to repeated washing with water and detergents. The paint is especially recommended as a primer before Primacol decorative effects such as: Silver Sand, Royal Silk, Mystic and Moonlight. It is also recommended for the effects obtained using the crackle-effect varnish and the decorative paper.

The paint is used to coat mineral and gypsum plasters, gypsum boards, bricks, wooden and wood-like surfaces as well as glass textile wallpapers.

APPLICATION For larger areas, use products from the same batch. Mix the paint thoroughly before use. Paint at the temperature of 10 °-30 °C. Apply 1-2 layer(s) at approx. 3-hour intervals.
Start painting the ceiling on the window-side and keep moving towards the center of the room in the direction of sunlight. Start painting the walls from places and corners that are difficult to access using a brush or a small thin roller. Apply the paint generously on the roller and distribute the paint on the substrate carefully and evenly. It is important not to paint with a dry roller. Do not stop painting the same area when started. Do not make any corrections when the coating is semi-dried. Join subsequent areas being painted "wet on wet". Every area of the surface must be finished by moving the roller always in the same direction. Ventilate the room after paining until the odour has gone.

SUBSTRATE PREPARATION The substrate to be painted should be stable, clean, dry and uniform. Fresh plasters can be painted after a 4 -week seasoning. Losses of material and cracks must be repaired and made even using filler putty.

STORAGE Store in the original, tightly closed container within the temperature range of 5 °-25 °C, in a dry area. Protect from direct sunlight.

SAFETY Keep out of reach of children. If swallowed, seek medical advice immediately and show this container or label. Contains a reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), 1,2-benzisothiazole 3 (2H) -one. May cause an allergic reaction.

PRIMACOL®
DECORATIVE

DECOBASE

PRODUCT DATA SHEET

UPDATE: 01.01.2022

TECHNICAL DATA

Color/ Form	Emulsion, colors according to the color card
Odour	Mild, specific
pH	8-9,5
Density	1,48 g/cm^3
Number of layers	1-2
Application of successive layer	3 h
Dry to touch	4-8 h

Completely dry	24 h
Tools	Brush, roller
Efficiency per 1 layer	up to 14 m^2/l
Thinner	water
Tool cleaning	Hot water
Voc limit	(Cat. A/a/FW)30g/l, the product contains < 30 g/l

LEGAL INFORMATION

The information contained in this technical data sheet provides recommendations and possible examples. The information provided reflects the current state of our knowledge and experience and does not free the user from the obligation to make his or her own tests to check the suitability of the product for the intended purpose. The manufacturer reserves the right to change this technical information without informing the client.