METALIQ PASTE

TECHNICAL DATA SHEET

UPDATE: 18.02.2022

BRAND **PRIMACOL®** DECORATIVE

PRODUCT **Metaliq paste**

- Steel wall effect



PACK **3,5 kg**

PROPERTIES **Metaliq Paste** is a black paste for indoor use. It is part of the Metaliq Kit. In combination with other products, it creates an aged metal effect in various shades.

SUBSTRATE PREPARATION The substrate should be clean, degreased, even, stable and not cracked. Fresh cement and cement-lime plasters should be seasoned for at least 4 weeks. The surface should be primed with the PRIMACOL® DECORATIVE primer. In order to reduce the consumption of Metaliq Paste, it is recommended to paint the substrate with Decobase D23 paint. After drying, gently wipe the wall with fine sandpaper grit 180 and then dust it.

APPLICATION To achieve a good appearance, the product should be used on very smooth surfaces. Failure to do so may result in blemishes and scratches.

Stir the product thoroughly after opening the packaging. Apply Metaliq Paste with a Venetian trowel. It is recommended to use tools with perfectly even and sharp edges. If necessary, the edge of the trowel can be sharpened with sandpaper 2000. Apply the product to the wall in horizontal and vertical movements to form a pattern. After drying (12h), carefully wipe the surface with fine sandpaper, then dedust and polish with a clean spatula. Depending on the Metaliq set, proceed to application of Metaliq Patine or Metaliq Top.

NOTE! Tools should be washed frequently during work to avoid scratches on the decorated surface caused by the residue of the dried product.

Always test the product on the main surface before use. The manufacturer accepts no responsibility for improper use of the product and does not guarantee that the effect will be identical to that shown on the samples. The effect obtained depends on many factors, such as the preparation of the substrate, the tools used, the application technique.

STORAGE Store the product in a tightly closed original container at 5 - 30°C and out of the reach of children. Do not expose it to sunlight. Protect from freezing.

SAFETY Product treated with biocidal product. Contains C(M) IT /MIT (3:1).

PRIMACOL® DECORATIVE

METALIQ PASTE

TECHNICAL DATA SHEET

UPDATE: 18.02.2022

Contains a reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) and 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

TECHNICAL DATA

Chemical composition	Water, polymer solution, fillers, additives	Tools	Venetian trowel
Color	Black	Touch dry	2-4 h
Odour	Mild, characteristic	Completely dry	24 h
Density	1,70 kg/dm^3	Coverage per packaging	10 m^2
Finish	Matte/ semi-matte/ gloss (depending on application technique)	Diluent	water
Number of layers	1	Tool cleaning	Water with detergent
Voc limit	(cat A/l/FW): 200 g/l, the product contains max. 200 g/l.		

LEGAL INFORMATION

The information contained in this technical data sheet provides recommendations and possible examples. The information provided reflects the current state of our knowledge and experience and does not free the user from the obligation to make his or her own tests to check the suitability of the product for the intended purpose. The manufacturer reserves the right to change this technical information without informing the client.