BRAND **PRIMACOL®** DECORATIVE

PRODUCT **Metaliq Top**

Metallic decorative paint

- Metallic decorative pant
- Steel wall effect



PACK **0,5 kg**

PROPERTIES **Metaliq Top** is a metallic paint for interior use. It forms the final decorative layer of the Metaliq kit. Once dried, it gives the surface the final steel effect. The paint is available in 5 colors.

APPLICATION It is recommended to use tools with perfectly even and sharp edges. If necessary, the edge of the trowel can be sharpened with sandpaper 2000. During work, tools should be frequently cleaned with water so that the remnants of the dried product do not leave scratches.

Stir the paint thoroughly after opening the packaging. Apply Metaliq Top with the spatula on the prepared surface. Spread the paint vertically and horizontally on the surface to be decorated and gather any excess product. Let the layer dry after finishing the work.

Always test the product on the main surface before use. The manufacturer accepts no responsibility for improper use of the product and does not guarantee that the effect will be identical to that shown on the samples. The effect obtained depends on many factors, such as the preparation of the substrate, the tools used, the application technique.

SUBSTRATE PREPARATION Depending on the Metaliq set, the substrate to be decorated with Metaliq Top should be prepared as described in Metaliq Paste / Metaliq Patine.

STORAGE Store the product in a tightly closed original container at 5 - 30°C and out of the reach of children. Do not expose it to sunlight. Protect from freezing.

SAFETY Product treated with biocidal product. Contains C(M) IT /MIT (3:1).
Contains a reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) and 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

TECHNICAL DATA

Chemical composition	Water solution of styrene-acrylic copolymer, fillers, additives	Completely dry	24 h

PRIMACOL®
DECORATIVE

METALIQ TOP

TECHNICAL DATA SHEET

UPDATE: 18.02.2022

Color	Iron, silver, brass, copper, gold	Touch dry	1-2 h
Odour	Mild, characteristic	Tools	Spatula
Density	1 kg/dm^3	Coverage per packaging	+/- 10 m²
Finish	Metallic, glossy	Diluent	Water
Number of layers	1	Tool cleaning	Water with detergent
Voc limit	(cat. A/l/WB): 200 g/l, the product contains max. 10 g/l.		

LEGAL INFORMATION

The information contained in this technical data sheet provides recommendations and possible examples. The information provided reflects the current state of our knowledge and experience and does not free the user from the obligation to make his or her own tests to check the suitability of the product for the intended purpose. The manufacturer reserves the right to change this technical information without informing the client.